M. Binkley, R. Madrak, K. Burkett, R. W. Wagner,

On July 15, 2004 several wire samples were taken to the TD SEM in Lab 3. Donna Hicks and Deepak Chichili operated the equipment.

The wire samples were mounted on an aluminum holder that was 2 inches in diameter. The wire samples were in the following order: reverse aged in SS tube, aged wire, new wire, reverse aged in GMC, and additionally aged in GMC. The new wire (in the center of the holder) was taken directly off a spool of new wire. All the aged wires started with a piece of wire taken from the higher z region of the wire plane removed from SL2 of the COT in March 2004. All the reverse aging was done with a Sr90 source. Under all conditions the Sr90 source was found to reverse age the wires irradiated by it. The reverse aging in the SS tube was done in exhaust gas from the COT in early July (argon/ethane plus1.7% isopropanol and about 100 ppm of O2). The wire that was reverse aged in the GMC was with argon/CO2 (80/20). The wire that was additionally aged in the GMC was away from the Sr90 source with argon/ethane plus 1.7% isopropanol with no added oxygen (however no measurement of the oxygen content was made).

All the SEM measurements were made with a 10 keV electron beam which always shows some of the gold beneath whatever coating there is on the wire. This electron beam was not energetic enough to see the tungsten of the wire unless the gold coating had been removed. The basic COT wire is 40 micron tungsten with about 0.5 gold coating.

The following pages show the EDS analysis of the wires. The following atomic percentages are observed:


New wire: 43% carbon and 57% gold

Aged wire: about 85% carbon, 4% oxygen, and 11% gold


Reversed aged SS tube: about 65-75% carbon, 25-35% gold and very I little oxygen.

Reverse aged GMC: Less carbon but more oxygen.


New wire




Aged Wire general area




Aged wire crater




Aged wire general area




EDS analysis of another general area on the aged wire near the center. Very similar to the previous general area on an aged wire,




Reverse aged in SS tube at center.




EDS analysis of the wire reverse aged in SS tube with COT exhaust gas (~100ppm of O2). Surface brighter than aged wire, but more carbon than on new




Reverse aged in SS tube at center.




EDS analysis of the wire reverse aged in SS tube with COT chamber exhaust. Wire surface looks brighter than age wire, but more carbon seen than on new wire.




Reverse aged in SS tube 6mm right of center.




Reverse aged in SS tube 20mm right of center




Reverse aged in SS tube 20mm right of center




Reverse aged in SS tube 30mm right of center




GMC wire with more aging shown at its center




Reverse aged GMC wire at the center (avg2)




Reverse aged GMC wire at the center (avg3)




Reverse aged GMC wire at the center (avg)



Wire reverse aged in GMC to the left of center



Wire reverse aged in GMC to the right of center



Dark spot to the right of center on wire reverse aged in GMC

